

**Solis**

**THE TOUGHEST  
PERFORMER  
FOR YOUR FIELD**

**26  
SHUTTLE XL**



**INTEGRATED  
LOADER  
JOYSTICK (OPTIONAL)**

**MULTI TIRE OPTIONS  
(AGRI, INDUSTRIAL  
& TURF TYRE)**

**QUICK ATTACHED  
LOADER**

**SYNCHROMESH  
SHUTTLE**

**9 FORWARD  
X 9 REVERSED GEAR**



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**

THE TOUGHEST  
PERFORMER  
« FOR YOUR FIELD »

**26**  
SHUTTLE XL

**Solis**



FEATURES	<b>26</b> SHUTTLE XL
<b>ENGINE</b>	
Engine Type	Mitsubishi 3-Cylinder Diesel Motor
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
<b>TRANSMISSION</b>	
Drive	4 WD
Clutch	Single Clutch
Gearbox	9 Forward + 9 Reverse
Front Axle	4WD
Transmission	Constant Mesh with Synchromesh Shuttle Lever
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	21,46 @2760 fly up
Minimum Speed (Km/Hr)	1,14@rated
<b>BRAKES</b>	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
Trailer load (unbraked)	1050 Kg
Inertia Braked	3000 Kg
Differential Lock	Yes, Foot Operated
<b>PTO</b>	
PTO (rpm)	540/540E
PTO (actuation)	Mechanical
<b>STEERING</b>	
Steering	Power steering
<b>ELECTRICAL</b>	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DA
Hydraulic Lifting Capacity	600 Kg
Lift Rods	Standard
Litre per Minute(LPM)	17.8

FEATURES	<b>26</b> SHUTTLE XL		
<b>SAFETY SWITCH</b>			
PTO Safety	Standard		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
<b>CAPACITY (LTRS)(+/-5%)</b>			
Fuel Tank (Lit)	20		
<b>TURNING RADIUS</b>			
Without brakes (m) as per standard tyres	3.02 (RHS), 3.15 (LHS)		
<b>TYRE</b>			
Front	6.00-12		
Rear	8.30-20		
<b>DIMENSION &amp; WEIGHT(+/-5%)</b>			
Weight (Kg)	1250		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (max)-1050 (min)		
Height (mm) Up to ROPS	2325		
Min Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	960		
<b>OTHERS</b>			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with std. Ballast	Front weights-2 x 15		
Trailer Hitch	Towbar, drawbar (optional)		
ROPS	Yes		
<b>OPTIONAL FEATURES</b>			
Cabin Option	Yes		
<b>Tyres</b>			
Radial Agri: Front   Rear 6,5/80-12 280/70 R18	Turf: Front   Rear 25x8,50-14 13.60-16	Ind: Front   Rear 23x8,50-12 33x15,50-16,5	GALAXY PRO R- 280/70R16
Front loader	YES optional		

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

**DEALER STAMP**



**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220 / 522222

Fax: 91- 01882-522222 | Email: exports@sonalika.com | URL: www.solistractors.com/www.solisworld.com