





FEATURES	50 Rops
ITL ENGINE 📸	
No. of cylinders / capacity (cc) / valves / emissions level	3/ 3065/ 4/ CRDi Stage V
After treatment system	DOC + DPF
Rated engine power (kw/Hp)	37.3/50
Rated engine speed	2000
Max. torque (Nm)	220@1400 Rpm
Aspiration	Turbo charged
Intercooler	Yes
Air Cleaner	Dual Stage Dry Type
Updraft Exhaust Pipe	Yes
Fuel tank capacity (L)	72
TRANSMISSION H	
12x12 Synchro Shuttle transmission (4WD)	Yes
Maximum forward speed	1.3kmph
Minimum forward speed	30kmph
FRONT AXLE	
4WD Front Axle	Yes
Differential Lock	Mechanical
4WD Actuation	Mechanical
Brake Actuation	Mechanical Assist
PTO 🌗	
PTO Type	Mechanical
540/540E	Yes
HYDRAULIC O 	
Hydraulic pump flow (lpm)	45
Open center mechanical draft control	Yes
Top link draft sensing	Yes
Liftomatic system	Yes
Lift Capacity	2500 KG
Linkage Category	1
Max. no. of rear remotes	2/3 (0)
Max. no. of Mid remotes	2
REAR HITCHES	
E-Mark Swinging Drawbar	Yes
TRAILER BRAKES	
Without Trailer Brakes	Yes
ELECTRICALS ()	
Battery	110AH 800CCA
Alternator	90A/120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven On Trailer Socket	Yes
OPERATOR ENVIRONMENT	
Suspended platform (with ROPS)	Yes

FEATURES	50 Rops
DIMENSIONS and	
Wheelbase (mm)	2225
Overall Height (mm)	2690/2480
Overall Width (mm)	1840-1880
Overall Length (mm)	3825-4055
Front Track Width (mm)	1570
Rear Track Width (mm)	1450
Ground Clearance (mm)	310
Unladen Mass (Kg)	2870
Tyre Combination	9.5x20 & 13.6x28

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221 Fax:+91- 01882-522222 | Email: info@solis.com | URL: www.solistractors.com